

ULTRA-LOK™ RSQ
SELF-RETRACTING LIFELINE WITH RESCUE

WORLD'S FIRST DUAL-MODE SELF RETRACTING LIFELINE



THE ULTIMATE IN FALL PROTECTION

PRODUCT SHEET

MULTIPLE BUILT-IN RESCUE OPTIONS FOR SUPERIOR SAFETY

DBI-SALA self retracting lifelines are the most technologically advanced fall protection devices available. The Ultra-Lok™ RSQ Self Retracting Lifeline offers a revolutionary design to allow the worker multiple options within one device, while offering the highest level of security and mobility.

The World's First Dual-Mode Operation


Our exclusive dual-mode operation allows the user, prior to connection, to choose between fall arrest requiring assisted rescue, or self rescue. This two-in-one operation allows the device to be optimised for the work site while providing the ultimate level of worker safety.

After setting the device mode, should a fall occur, the following will happen:



Fall Arrest Mode (Assisted Rescue):

A speed sensing brake stops the fall, reduces forces imposed on the user to safe levels of 6kN or less and allows for assisted rescue to take place.



Automatic Rescue Mode (Self Rescue/Descent):

A speed sensing brake stops the fall just like in fall arrest mode, then instantly a centrifugal brake activates lowering the user at a controlled speed to the next level or ground.



3504555
Ultra-Lok™ RSQ
Self Retracting
Lifeline



3500100
Assisted Rescue
Tool Only

3500102
First-Man-Up™
Pole with Assisted
Rescue Tool



Fall Arrest Mode
Assisted
Rescue
by Pole



Fall Arrest Mode
Assisted
Rescue
by Hand



Automatic Rescue
Mode
Self Rescue/
Descent



These Assisted Rescue Options "Engage" the Automatic Rescue Mode.
Traditional assisted rescue operations may also be conducted.

Ultra-Lok™ RSQ Models

3504555: Ultra-Lok™ RSQ Self Retracting Lifeline with Rescue,
15m length, stainless steel cable and hook

Accessories

3500100: Assisted Rescue Tool (if you already have a First-Man-Up™ Pole)
3500102: First-Man-Up™ Pole (2.4 - 4.8m) with Assisted Rescue Tool

DBI-SALA rescue equipment is manufactured in a wide variety to suit your specific needs and applications, visit www.capitalsafety.com to view our entire range.

Specifications:

Rated Capacity: One user - 34kg to 141kg. Maximum Arresting Force: 6kN. Descent Speed: 1 m/s. Length of Lifeline: 15m. Unit Dimensions: H - 29cm, W - 20cm, D - 9cm. Weight: 8.5kg. Power Spring: Stainless steel. Locking Pawls and Springs: Stainless steel. Ratchet Plate: Stainless steel. Anchorage Loop: Zinc plated steel. Drum: Aluminium. Load Straps: Zinc plated steel. Housing Material: 2 pieces, thermoplastic composite. Lifeline Material: 5mm, 7x19 stainless steel cable. Snap Hook: Stainless steel, fall indicating, self locking and swiveling, 22.2kN tensile strength. Compatibility: Capital Safety rescue equipment are compatible for use with DBI-SALA and PROTECTA approved components and systems, or as recommended by a competent person. Standards: Meets CE EN 360, EN341 and complies with AS/NZS 1891.3. Country of Origin: U.S.A. Special Instructions/Conditions of Use: Reading user instruction manual prior to use is essential.



Capital Safety - Australia & New Zealand
Australia: 1800 245 002 | New Zealand: 0800 212 505
www.capitalsafety.com.au
sales@capitalsafety.com.au

