

- ✓ Extra bund capacity in small areas
- ✓ “No Bounce” Drive-Over Bunding

FLEXIBLE FLOOR BUNDING

VERSATILE AND STURDY FLOOR BUNDING



Product	Code	Length	Width	Height
Flexible Floor Bunding	CHFFB03	5m	205mm	75mm
Flexible Floor Bunding	CHFFB01	10m	205mm	75mm
Flexible Floor Bunding	CHFFB02	30m	205mm	75mm
90° Corner Join	CHFFB04	.55m	205mm	75mm
Installation Kit 5ml	CHFFB06	Rubber Strip, Concrete Fasteners and Adhesives		
Installation Kit 10ml	CHFFB05			
Installation Kit 90° Corner Join	CHFFB08			

APPLICATION EXAMPLES:

- Warehouses
- Across doorways and access points
- Hazardous liquid storage areas
- Work shops
- Wash Bays

Flexible Floor Bunding is manufactured from purpose extruded foam encased in heavy-duty PVC. The triangular profile collapses down as vehicles drive over it and then springs back to shape after the vehicle passes. This allows for a steady pass for forklifts without compromising their load as they cross the banded section.

This bund type is manufactured in a standard 75mm height which generates greater containment capacity in the case of small banded areas.

Before purchasing floor bunding ensure you check ground clearance of forklifts.

Manufactured using heavy duty, high visibility 900gsm PVC. The material has very good chemical resistance and durability.

Installation Kit Available. For each 10m length you will require:

- 2x tubes of adhesive sealant

Optional:

- 70 x fasteners (5mm x 38mmD)
- 20m of rubber insertion strip (10mL rolls)

