

1470 Protector Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Double safety locking latches with keys
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1470 Standard



1470NF No Foam



1470WF With Foam

DIMENSIONS

Interior (L×W×D)	15.70 x 10.70" x 3.87 (39.9 x 27.2 x 9.8 cm)
Exterior (L×W×D)	16.88 x 13.23" x 4.47 (42.9 x 33.6 x 11.4 cm)
Lid Depth	1.47" (3.7 cm)
Bottom Depth	2.40" (6.1 cm)
Total Depth	3.87" (9.8 cm)
Int Volume	0.38 ft³ (0.011 m³)
Padlock Hole Diameter	0.25" (0.6 cm)

MATERIALS

Body	ABS		
Latch	ABS		
O-Ring	Polymer		
Pins	Stainless Steel		
Foam	1.3 lb Polyurethane		
Purge Body	ABS		

Purge Vent

3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

Weight With Foam	5.51 lbs (2.5 kg)		
Weight Empty	4.28 lbs (1.9 kg)		
Buoyancy	24.91 lbs (11.3 kg)		
Master Pack Weight	22.20 lbs (10.1 kg)		

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

MIL C-4150J

OTHER

Master Pack	4		
Nameplate	yes		
Military	yes		

ACCESSORIES





1471 3 pc. Replacement Foam Set

1472 Shoulder Strap



1473 Replacement O-ring



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 07-02-24