



— PRODUCT DATA SHEET

P5R



P5R

PRODUCT DESCRIPTION

Do you need a light to shine your way through the park at night or keep you company when you are working in the house or garden? The Ledlenser P5R is a strong option. The compact yet powerful flashlight has a focus function to adapt the light to each range and use case. You can also use both rechargeable and disposable batteries and easily operate the flashlight with one button. And: The high-quality housing is made of 75 % recycled aluminium.



- Compact rechargeable flashlight with focus function (Advanced Focus System)
- Dual Power Source: Operates with rechargeable or disposable batteries, charging via USB-C (charging cable not included)
- Intuitive operation with one button
- Sustainable: Use of 75 % recycled aluminium⁹ and 7-year warranty*
- Element-proof: High water and dust resistance (IP68)

TECHNICAL DATA	
Weight incl. batteries [g]	99
Material	Aluminum alloy
Length [mm]	121
Length (focused) [mm]	125
Tube diameter [mm]	22
Head diameter [mm]	30

POWER SUPPLY	
Battery quantity	1
Rechargeable	Yes
Battery type	Lithium-ion
Total battery voltage [V]	3,7
Total battery capacity [mAh]	920
Total battery energy [Wh]	3,404 Wh
Battery replaceable	Yes
Charging time [min]	180
Useable batteries	Mignon (AA) 1.5V, AA NiMH 1.2V
Energy status indicator	Battery Indicator, Charge Indicator, Low Battery Warning

FEATURES

Transportation Lock

FURTHER SPECIFICATIONS	
IP class	IP68
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Cool White Main: Boost, Power, Mid power, Low power

LIGHT SOURCE	MAIN
Amount LEDs	1
Color	Cool White
Color temperature [K]	6000 to 7500
Color rendering index (CRI)	70

LIGHT VALUES - Cool White Main

	Boost	Power	Mid power	Low power
Light output [lm]	750	350	100	25
Beam distance [m]	280	180	100	50
Run time [h]	-	1	4	20

SWITCH

Front Switch

TECHNOLOGIES

Advanced Focus System, Temperature Control System, Flex Sealing Technology, Dual Power Source



— P5R

PACKAGING AND LOGISTICS



For illustration purposes only

PACKAGING INFORMATION

Type of packaging	Box
Scope of delivery	Adjustable Lanyard, 14500 Li-ion rechargeable battery
Item No.	ZL 503109
Color	Black
Cost Price / RRP	Check Zenport for latest pricing

SINGLE PACKAGE

Dimensions W x H x D [cm]	14.5 x 8.5 x 4.2
Gross weight [g]	171
GTIN-13	4058205037310

EXPORT CARTON

Unit	24
Dimensions W x H x D [cm]	37.5 x 17 x 31
Gross weight [g]	4760
GTIN-13	4058205037297

— P5R

PRODUCT SERIES

Powerful flashlights for those who push boundaries—the discerning enthusiasts, the industrious workers, the bold adventurers and the forward-thinkers. Lights that bridge the gap between the epic and the technical. In your hand, they do more than shine—they guide your path, reveal the unknown and empower you to explore, discover and redefine what is possible. Pioneering Brilliance. The P-Series: Redefined.

— P5R

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

*) 7 year warranty only if registered, otherwise 2 years. Warranty conditions viewable at <https://ledlenser.com/en/infos-service/warranty/>

1) Measured values according to ANSI/PLATO FL 1 in the respective setting named. If no setting is specifically named, the luminous flux (lumens/lm) and range (meters/m) values refer to the brightest setting and the burn time

(hours/h) values refer to the lowest setting. A boost function (if available) can be used several times, but is only available for a short time at a time. In case the lamp is equipped with colored LED(s), the measured values are given with white light or the white LED. If the lamp has different energy modes, the "energy saving mode" is the basis for the measurement.

2) Calculated value of the capacity in watt-hours (Wh). This applies to the battery(ies) contained in the delivery condition of the respective item or, in the case of lamps with rechargeable battery, to the battery(ies) contained herein in a fully charged condition.

9) All aluminium components are made of at least 75 % recycled aluminium and may thus vary in surface structure and color.